TABLE I:	fibre sources
Country:	United Kingdom
Year:	2011

							For all purpo	ses, r	not only energ	ду		For EU 27 Member countries	
	Fibre SOURCES		Fibre TYPES			Domestic production		Imports		Exports		Gross Domestic supply	Imports from EU 27 countries
							DQ		<u>DQ</u>		<u>DQ</u>		DQ
	Woody		Industrial Rou	ndwood (C & NC)	m³	8,788	0	602	0	578	0	8,811	587 O
	biomas	Biomass from	Fuelwood (C &	NC)	m³	1,234	0	11	0	146	0	1,099	9 0
		Forests		of which from short rotation coppice	m³							-	-
	Forests Woody		Industrial Roundwood (C & NC)										
	Primary	Biomass Outside	Fuelwood (C &		m³	1,438	С					1,438	
	P.	Forests		of which from short rotation coppice	m³							,	
ces	ste s)		Solid	Chips and particles	m³	2,309	0	116	0	234	0	2,192	116 O
log I	waste ucts)		co-products	Wood residues	m³	770	0	1,527	0	516	0	1,782	189 O
S p	tral	Forest based Industry	(C & NC)	Bark	m³	1,029	С					1,029	
Wood Source:	ndustral waste (co-products)		Liquid co-products	Black liquor (without crude tall oil)	t	0							
	<u>د</u> ي		(C & NC)	Crude tall oil	t			17	0	1	0	15	
'	Municipal solid waste biodegradable	Wood waste	Post consumer	Non-hazardous wood waste	t	4,327	С					4,327	
	Muni solid v biodegr	Wood waste	recovered wood	Hazardous wood waste	t								
			Wood from un	known sources	m³								

© 2012 UNECE/FAO Forestry and Timber Section - In case of any uncertainties or questions on the JWEE 2011 please contact woodenergy.timber@unece.org

Pr	oposed Data Sources:
	JFSQ 2011 Provisional
	Calculated - based on JFSQ data and conversion factors
	National waste statistics: OECD link / Basel Co / EUROSTAT link
	National (empirical) sources / studies
	(Inter-) National energy statistics

Units:
t = metric tonnes [megagram]
m³ = solid cubic metre, underbark
bv = m³ bulk volume
rwe. = Roundwood equivalent in m ³
L = Litre
t d.m. = Metric tonnes dry matter

TABLE II: processed wood-based fuels					
Country:	United Kingdom				
Year:	2011				

	Fibre TYPES		Original unit	Domestic production		Import		Export		Gross Domestic supply
			-	-	<u>DQ</u>		DQ		<u>DQ</u>	
		Wood Charcoal	t (thousand)	5	0	62	0	2	0	66
	Processed solid biofuels from wood	Wood Pellets	t (thousand)	244	0	1,015	0	38	0	1,221
Processed		Wood Briquettes	t (thousand)							
wood-based	Processed liquid biofuels from wood	Pyrolysis Oils	L (million)							
fuel production		Cellulose based ethanol	L (million)	:		:				
		Wood based biodiesel	L (million)							
	Gaseous Wood- based Fuels	Synthesis Gas								

© 2012 UNECE/FAO Forestry and Timber Section - In case of any uncertainties or questions on the JWEE 2011 please contact: woodenergy.timber@unece.org

Prop	osed Data Sources:
	JFSQ 2011 Provisional
	Calculated - based on JFSQ data and conversion factors
	National waste statistics: OECD / Basel Conventio / EUROSTAT
	National (empirical) sources / studies
	(Inter-) National energy statistics

Units:	
t = metri	c tonnes [megagram]
m³ = sol	id cubic metre, underbark
bv = m³	bulk volume
rwe. = R	oundwood equivalent in m ³
L = Litre	
t d.m. =	Metric tonnes dry matter

Energy use of wood fibres by ISIC-sectors (in 1000 t.d.m or t) TABLE IV: energy use Country: **United Kingdom** Year: 2011 For all purposes, not only energy **Energy Transformation Sector** Autoproducer Heat, CHP and Electricity Gross Transfor-Main Activity Producer Unit **Net Domestic** (include autoconsumed heat!) Domestic mation [1 000] Pulp & Paper Wood & wood supply Total Other supply (table TIII) Electricity CHP Heat Total [ISIC No.21] products DQ Woody Biomass from Forests 506 62 С 68 С 130 t d.m. 506 С Primary solid С Woody Biomass Outside Forests t d.m. 1 1 0 biomass Unspecified 0 ... t d.m. 0 0 0 С С 688 Chips and particles 514 -86 428 254 254 688 t d.m. Solid Wood residues t d.m. 390 0 27 С 27 0 390 co-products С Bark 463 0 463 44 44 0 ... (C & NC) t d.m. Forest based Unspecified solid co-products 0 0 53 С 53 t d.m. 0 Industry Black liquor (without crude tall oil) 0 0 0 0 0 Liquid 0 С С co-products Crude tall oil t 15 15 89 89 4 ... (C & NC) Unspecified liquid co-products 0 0 0 Wood Charcoal t d.m. 62 62 0 0 ... Processed solid 1,188 biofuels from Wood Pellets 1,099 1,099 С t d.m. 1,188 wood Processed wood-Wood Briquettes t d.m. 0 0 based fuel Pyrolysis Oils 0 0 production 0 Processed liquid biofuels from Cellulose based ethanol 0 0 0 wood Wood based biodiesel 0 0

3,245

0

0

-16

0

0

0

3,230

0

0

0

113 C

113

0

0

0

0

0

0 ...

t d.m.

t d.m.

t d.m.

t d.m.

Non-hazardous wood waste

Hazardous wood waste

Unspecified wood waste

Post consumer

recovered wood

Wood from unknown sources

^{© 2012} UNECE/FAO Forestry and Timber Section - In case of any uncertainties or questions on the JWEE 2011 please contact woodenergy.timber@unece.org

Energy use of wood fibres by ISIC-sectors (in 1000 t.d.m or t) (cont'd)

			Direct final con	sumption		
Residentia	-	Agriculture, Forestry and Fishing	Commercial and Public services	Transport Sector	Other	Total
	<u>DQ</u>	DQ	DQ	<u>DQ</u>	DQ	DQ
717	С					717
358	С					358
						0
						0
						0
						0
		:				0
						0
						0
						0
62	С					62
			82 C			82
						0
		:				0
						0
						0
						0
						0
						0
]		0

Data Qualities**:	
Α	Excelllent data quality (e.g. empirical data from a recent study)
В	Good data quality (e.g. older studies with widely recognized precision or a good expert estimate -based on more than one source)
С	Rough estimate (about right order of magnitude),
D	No information on data quality available
0	Official national statistics

**The "DQ" - Data Quality indicator shall enable correspondents to submit different information form different data sources which implies different qualities.

C & NC	Coniferous and non-coniferous.	
m ³	Cubic metres solid volume excluding bark.	
Woody biomass	Cubic metres solid volume excluding bark.	
Woody Biolinass	Organic woody material both above-ground and below-ground, and both living and dead, measured to a minimum diameter of 0 mm (diameter breast height). Includes stem, stump, branches, bark, seeds and foliage, roots, shrubs and bushes. Excludes: litter (definition of "biomass" in FAO 2004, which is based on IPCC Good Practice Guidelines LULUCF Glossary 2003; term "woody" added, minimum diameter threshold as in TBFRA 2000).	MCPFE "STATE OF EUROPE'S FORESTS 2007"
Above-ground (living) woody biomass	All living woody biomass above the soil, including stem, stump, branches, bark, seeds and foliage. (FAO 2004, based on IPCC Good Practice Guidelines LULUCF Glossary 2003; term "woody" added).	MCPFE "STATE OF EUROPE'S FORESTS 2007"
Below-ground (living) woody biomass	All living woody biomass of live roots and the below-ground part of the stump. (FAO 2004, based on IPCC Good Practice Guidelines LULUCF Glossary 2003; term "woody" added).	MCPFE "STATE OF EUROPE'S FORESTS 2007"
Forest	Land spanning more than 0.5 hectares with trees higher than 5 meters and a canopy cover of more than 10 percent, or trees able to reach these thresholds in situ. It does not include land that is predominantly under agricultural or urban land use. Explanatory notes:	
	 Forest is determined both by the presence of trees and the absence of other predominant land uses. The trees should be able to reach a minimum height of 5 meters in situ. Areas under reforestation that have not yet reached but are expected to reach a canopy cover of 10 percent and a tree height of 5 m are included, as are temporarily unstocked areas, resulting from human intervention or natural causes, which are expected to regenerate. Includes areas with bamboo and palms provided that height and canopy cover criteria are met. Includes forest roads, firebreaks and other small open areas; forest in national parks, nature reserves and other protected areas such as those of specific scientific, historical, cultural or spiritual interest. Includes windbreaks, shelterbelts and corridors of trees with an area of more than 0.5 ha and width of more than 20 m. Includes plantations primarily used for forestry or protection purposes, such as rubberwood plantations and cork oak stands. Excludes tree stands in agricultural production systems, for example in fruit plantations and agroforestry systems. The term also excludes trees in urban parks and gardens. 	FAO 2004 - Global Forest Resources Assessment Update 2005 – Terms ar Definitions
Short rotation coppice	(coppice forest) Woodland which has been regenerated from shoots formed at the stumps of the previous crop trees, root suckers, or both, i.e., by vegetative means. Normally grown on a short rotation for small material, but sometimes, e.g. some eucalypt species, to a substantial size.	<u>IUFRO</u> <u>Silva Term Database</u>
Woody Biomass Outside Forests	Any woody biomass outside areas defined as "Forest". It includes woody biomass form "Other wooded land" and "Trees outside forests".	
Other Wooded Land	Land not classified as "Forest", spanning more than 0.5 hectares; with trees higher than 5 meters and a canopy cover of 5-10 percent, or trees able to reach these thresholds in situ; or with a combined cover of shrubs, bushes and trees above 10 percent. It does not include land that is predominantly under agricultural or urban land use.	FAO 2004 - Global Forest Resources Assessment Update 2005 – Terms at Definitions
Trees outside forests	Includes all trees found outside forests and outside other wooded lands: - stands smaller than 0.5 ha; - tree cover in agricultural land, e.g. agro forestry systems, home gardens, orchards; - trees in urban environments; - along roads and scattered in the landscape.	FAO 2004 - Global Forest Resources Assessment Update 2005 – Terms an Definitions
Industrial Roundwood (C & NC)	Coniferous and non-coniferous Industrial Roundwood: All roundwood except wood fuel. It is an aggregate comprising sawlogs and veneer logs; pulpwood, round and split; and other industrial roundwood. It is reported in cubic metres solid volume under bark (i.e. excluding bark). The customs classification systems used by most countries do not allow the division of Industrial Roundwood trade statistics into the different end-use categories that have long been recognized in production statistics (i.e. sawlogs and veneer logs, pulpwood and other industrial roundwood). () It excludes: telephone poles.	UNECE/FAO/EUROSTAT/ITTO JOINT FOREST SECTOR QUESTIONNAIRE DEFINITIONS 1.2
Fuelwood (C & NC)	Coniferous and non-coniferous Industrial Roundwood: Roundwood that will be used as fuel for purposes such as cooking, heating or power production. It includes wood harvested from main stems, branches and other parts of trees (where these are harvested for fuel) and wood that will be used for charcoal production (e.g. in pit kilns and portable ovens). The volume of roundwood used in charcoal production is estimated by using a factor of 6.0 to convert from the weight (t) of charcoal produced to the solid volume (m²) of roundwood used in production. It also includes wood chips to be used for fuel that are made directly (i.e. in the forest) from roundwood. It excludes wood charcoal. It is reported in cubic metres solid volume underbark (i.e. excluding bark). It includes wood fibres gained from used logging residues and thinnings.	UNECE/FAO/EUROSTAT/ITTO JOINT FOREST SECTOR QUESTIONNAIRE DEFINITIONS 1.1

	UNECE/FAO/EUROSTAT/ITTO
Wood that has been reduced to small pieces and is suitable for pulping, for particle board and/or fibreboard production, for use as a fuel, or for other purposes. It excludes wood chips made directly in the forest from roundwood (i.e. already counted as pulpwood, round and split). It is reported in cubic metres solid volume excluding bark.	JOINT FOREST SECTOR QUESTIONNAIRE DEFINITIONS 3.
The volume of roundwood that is left over after the production of forest products in the forest processing industry (i.e. forest processing residues) and that has not been reduced to chips or particles. It includes sawmill rejects, slabs, edgings and trimmings, veneer log cores, veneer rejects, sawdust, residues from carpentry and joinery production, etc. It excludes wood chips made either directly in the forest from roundwood or made from residues (i.e. already counted as pulpwood, round and split or wood chips and particles). It is reported in cubic metres solid volume excluding bark.	UNECE/FAO/EUROSTAT/ITTO JOINT FOREST SECTOR. QUESTIONNAIRE DEFINITIONS 4.
E.g. European Waste 03 01 01 Waste bark and cork It is reported in cubic metres solid volume.	
Alkaline spent liquor obtained from digesters in the production of sulphate or soda pulp during the process of paper production, in which the energy content is mainly originating from the content of lignin removed from the wood in the pulping process.	Unified Bioenergy Terminology - UBET (FAO)
Tall oil, also called liquid rosin or tallol, is a viscous yellow-black odorous liquid obtained as a byproduct of the Kraft process of wood pulp manufacture. The name originated as anglicization of Swedish "tallolja" ("pine oil"). Crude tall oil contains rosins, unsaponifiable sterols (5-10%), resin acids (mainly abietic acid and its isomers), fatty acids (mainly palmitic acid, oleic acid and linoleic acid), fatty alcohols, some sterols, and other alkyl hydrocarbon derivates. By fractional distillation tall oil rosin is obtained, with rosin content reduced to 10-35%. By further reduction of the rosin content to 1-10%, tall oil fatty acid (TOFA) can be obtained, which is cheap, consists mostly of oleic acid, and is a source of volatile fatty acids. The rosin finds use as a component of adhesives, rubbers, and inks, and as an emulsifier. The pitch is used as a binder in cement, an adhesive, and an emulsifier for asphalt. TOFA is a low-cost alternative to tallow fatty acids for production of soaps and lubricants. When esterified with pentaerythritol, it is used as a compound of adhesives and oil-based varnishes. All the above tall oil components should be reported under this category, despite the fact that a very limited number of countries may have different tax schemes for each tall oil	<u>Wikipedia</u>
Used wood arising from construction of buildings or from civil engineering works. Recovered wood from transport (pallets), private households, as well as used wood arising from construction or demolition of buildings or from civil engineering works.	<u>Unified Bioenergy Terminology - UBET</u> (FAO)
Waste produced by households, industry, hospitals and the tertiary sector which contains biodegradable materials ().	IEA Balance builder
Post-consumer recovered wood generated by any ISIC Sectors (Rev. 3.1) EXCEPT wood wastes generated by ISIC 02 , ISIC 2010 and ISIC 21 (corresponding to European Waste Classification 21.03 01 01 Waste bark and cork; 03 01 02 Sawdust; 03 01 03 Shaving, cuttings, spoiled timber/particle board/veneer; 03 01 99 Wastes not otherwise specified) This comprises: PACKAGING: (e.g. European Waste Classification (EWC) 15 01 03) Wooden packaging; CONSTRUCTION AND DEMOLITION WASTES (INCLUDING ROAD CONSTRUCTION): (e.g. EWC) 17 02 01 Wood	European Waste List
MUNICIPAL WASTES AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES INCLUDING SEPARATELY COLLECTED FRACTIONS: (e.g. EWC 20 01 07) Wood Please note that wood in mixed-waste streams that are burnt should be included where possible.	
Same definition and scope as non-hazardous wood waste. Hazardous waste as defined in ANNEX I & II in the Basel convention on transboundary movements of hazardous wastes and their disposal (www.basel.int). This definition shall be expanded to national waste classifications, if possible.	Basel Convention
	The volume of roundwood that is left over after the production of forest products in the forest processing industry (i.e. forest processing residues) and that has not been reduced to chips or particles. It includes sawmill rejects, slabs, edgings and trimmings, veneer log cores, veneer rejects, sawdust, residues from carpentry and joinery production, etc. It excludes wood chips made either directly in the forest from roundwood or made from residues (i.e. already counted as pulpwood, round and split or wood chips and particles). It is reported in cubic metres solid volume E.g. European Waste 03 01 01 Waste bark and cork It is reported in cubic metres solid volume. Alkialine spent liquor obtained from digesters in the production of sulphate or soda pulp during the process of paper production, in which the energy content is mainly originating from the content of lignin removed from the wood in the pulping process. Tall oil, also called liquid rosin or tailol, is a viscous yellow-black odorous liquid obtained as a byproduct of the Kraft process of wood pulp manufacture. The name originated as anglicization of Swedish "tailolgia" ("pine oil"). Crude tall oil contains rosins, unsaponifiable sterols (5-10%), resin acids (mainly abletic acid and its isomers), fatty acids (mainly palmitic acid, oleic acid and linoleic acid), fatty alcohols, some sterols, and other alighly hydrocarbon derivates. By fractional distillation tall oil rosin is obtained, with rosin content reduced to 10-35%. By further reduction of the rosin content to 1-10%, tall oil latty acid (TOFA) can be obtained, which is cheap, consists mostly of olici acid, and is a source of volatiently acids. The rosin finds use as a compound of adhesives, rubbers, and links, and as an emulalifier for apshala. TOFA is a low-cost alternative to tailow fatty acids for production of soaps and lubricants. When esterfield with pentaepsthic, it is used as a compound of adhesives and oil-based varnishes. All the above tall oil components should be reported under this

PROCESSED-W	VOOD BASED FUELS:	
	Secondary (processed) biofuels in the form of solids (e. g. charcoal), liquids (e. g. alcohol, vegetable oil), or gases (e. g. biogas as a mixture of methane and carbon dioxide), can be used for a wider range of applications with higher efficiency rates on average, including transport and high-temperature industrial processes.	Unified Bioenergy Terminology - UBET (FAO)
Wood Charcoal	Wood carbonized by partial combustion or the application of heat from external sources. It includes charcoal used as a fuel or for other uses, e.g. as a reduction agent in metallurgy or as an absorption or filtration medium. It is reported in metric tonnes.	UNECE/FAO/EUROSTAT/ITTO
	ATTENTION: In CA and US wood charcoal is often referred to as "Briquettes" - This must not be confused with Wood Briquettes as defined below!	JOINT FOREST SECTOR QUESTIONNAIRE DEFINITIONS 2.
Wood Pellets	Wood pellets is a fuel product compressed from milled wood. Raw materials are cutter shavings and sawdust, which are by-products of the mechanical wood-processing industry. (Combined Nomenclature 2009)	
	Introduction of a new additional note to (Combined Nomenclature) chapter 44:	Eurostat / CN 2009
	For the purposes of (CN) subheading 4401 30 20, the expression 'pellets' means cylindrical products which have been agglomerated either directly by compression or by the addition of a small quantity of binder, having a diameter not exceeding 25 mm and a length not exceeding 45 mm.	
Wood Briquettes	Densified biofuel made with or without pressing aids in the form of cubiform or cylindrical units, produced by compressing pulverized biomass. The raw material for briquettes can be woody biomass () are usually manufactured in a piston press. The total moisture of the biofuel briquette is usually less than 15 % of mass. (The JWEE assumes water content of 8 %)	Unified Bioenergy Terminology - UBET
	ATTENTION: In the US/CA this item is often referred to as "Pressed Logs" or any other compressed wood products for burning purposes. 2002 NAICS No. 321999: "Pressed logs of sawdust and other wood particles, nonpetroleum binder, manufacturing."	(FAO)
Biofuel	Any solid, liquid or gaseous fuel produced from biomass.	FAO Forestry Paper 154 Forests and energy
Second-generation biofuel	Fuels produced from cellulosic materials, crop residues and agricultural and municipal wastes.	FAO Forestry Paper 154 Forests and energy
Pyrolysis	Pyrolysis is thermal degradation either in the complete absence of oxidizing agent, or with such a limited supply that gasification does not occur to an appreciable extent or may be described as partial gasification. Relatively low temperature are employed of 500 to 800 °C, compared to 800 to 1000 °C in gasification.	FAO 1996
Pyrolysis Oil	Bio-oil produced by fast pyrolysis of biomass. A dark brown, mobile liquid containing much of the energy content of the original biomass, with a heating value about half that of conventional fuel oil. Can be burned directly, either alone or co-fired with other fuels, gasified or otherwise upgraded. Conversion of raw biomass to pyrolysis oil represents a considerable increase in energy density and it can thus represent a more efficient form in which to transport it.	UK Biomass Energy Centre
Cellulose based ethanol	Biogasoline (IEA) - Includes bioethanol (ethanol produced from (woody) biomass (), biomethanol (methanol produced from (woody) biomass(), bioETBE (ethyl-tertio-butyl-ether produced on the basis of bioethanol; the percentage by volume of bioETBE that is calculated as biofuel is 47%) and bioMTBE (methyl-tertio-butyl-ether produced on the basis of biomethanol: the percentage by volume of bioMTBE that is calculated as biofuel is 36%). Biogasoline includes the amounts that are blended into the gasoline - it does not include the total volume of gasoline into which the biogasoline is blended.	IEA Balance builder
Wood based biodiesel	Includes biodiesel (a methyl-ester produced from woody biomass, of diesel quality), biodimethylether (dimethylether produced from biomass), Fischer Tropsch (Fischer Tropsch produced from biomass), () and all other liquid biofuels which are added to, blended with or used straight as transport diesel. Biodiesel includes the amounts that are blended into the diesel - it does not include the total volume of diesel into which the biodiesel is blended.	IEA Balance builder
Synthesis Gas	A mixture of carbon monoxide (CO) and hydrogen (H2) which is the product of high temperature gasification of organic material such as biomass. Following clean-up to remove any impurities such as tars, synthesis gas (syngas) can be used to synthesize organic molecules such as synthetic natural gas (SNG - methane (CH4)) or liquid biofuels such as synthetic diesel (via Fischer-Tropsch synthesis).	UK Biomass Energy Centre

ENERGY USE:		
ISIC Rev. 3.1	International Standard Industrial Classification of all economic activities. Revised version 3.1.	United Nations Statistical Division
NACE 1.1	Statistical Classification of Economic Activities in the European Community, Rev. 1.1 (2002) - corresponds to ISIC at 4 digit level	Commission of the European Communities (Statistical Office/Eurostat)
CN	8 digit code - The Combined Nomenclature(CN) is comprised of the Harmonized System (HS) nomenclature with further Community subdivisions. The CN also include preliminary provisions, additional section or chapter notes and footnotes relating to CN subdivisions. Each CN subdivisions has an eight digit code number, the CN code, followed by a description.	European Commission Taxation and Customs Union
HS	6 digit code - The Harmonized Commodity Description and Coding Systems generally referred to as "Harmonized System" or simply "HS" is a multipurpose international product nomenclature developed by the World Customs Organization (WCO) corresponds to CN at 6 digit level.	World Customs Organization - WCO
Energy Transformation Sector	The transformation sector comprises the conversion of primary forms of energy to secondary and further transformation (e.g. coking coal to coke, crude oil to petroleum products, heavy fuel oil to electricity).	IEA Balance builder
Electricity	Electricity generated shows the total number of GWh generated by thermal power plants separated into electricity plants and CHP plants, as well as production by nuclear and hydro, geothermal, etc To be converted to TJ in the Joint Wood Energy Enquiry.	IEA Balance builder
Heat	Heat generated shows the total amount of TJ generated by power plants separated into CHP plants and heat plants.	IEA Balance builder
СНР	Combined Heat and Power generation. Combined heat and power plants (refers to plants which are designed to produce both heat and electricity). UNIPEDE refers to these as co-generation power stations. If possible, fuel inputs and electricity/heat outputs are on a unit basis rather than on a plant basis. However, if data are not available on a unit basis, the convention for defining a CHP plant noted above should be adopted.	IEA Balance builder
Main Activity Producer	Main Activity Plants plants refers to plants which are designed to produce electricity/CHP or Heat only. If one or more units of the plant is a CHP unit (and the inputs and outputs can not be distinguished on a unit basis) then the whole plant is designated as a CHP plant. Main activity supply undertakings generate electricity and/or heat for sale to third parties, as their primary activity. They may be privately or publicly owned. Note that the sale need not take place through the main activity grid. This includes district heating by communities, and small producers.	IEA Balance builder
Autoproducer	Autoproducer undertakings generate electricity and/or heat, wholly or partly for their own use as an activity which supports their primary activity. They may be privately or publicly owned.	IEA Balance builder
Final consumption	The term final consumption (equal to the sum of end-use sectors' consumption) implies that energy used for transformation and for own use of the energy producing industries is excluded. Final consumption reflects for the most part deliveries to consumers (see note on stock changes). In final consumption, petrochemical feedstock are covered under industry as an of which item under chemical industry for those oil products that are principally used for energy purposes. Separated from these are the other oil products that are mainly used for non-energy purposes (see non-energy use), which are shown in the rows for non-energy uses and included only in total final consumption. Backflows from the petrochemical industry are not included in final consumption.	IEA Balance builder
Paper, Pulp and Print:	[ISIC Divisions 21 and 22].	IEA Balance builder
Nood and Wood Products:	Wood and wood products (other than pulp and paper) [ISIC Division 20].	IEA Balance builder
Residential	All consumption by households, excluding fuels used for transport. Includes households with employed persons (ISIC Division 95) which is a small part of total residential consumption.	IEA Balance builder
Agriculture, Forestry and Fishing	Agriculture/Forestry includes deliveries to users classified as agriculture, hunting and forestry by the ISIC, and therefore includes energy consumed by such users whether for traction (excluding agricultural highway use), power or heating (agricultural and domestic) [ISIC Divisions 01 and 02]. Fishing includes fuels used for inland, coastal and deep-sea fishing. Fishing covers fuels delivered to ships of all flags that have refueled in the country (including international fishing) as well as energy used in the fishing industry [ISIC Division 05]. Previously fishing was included with agriculture/forestry and this may continue to be the case for some countries.	IEA Balance builder
Commercial and Public services	All activities coming into ISIC Divisions 41, 50, 51, 52, 55, 63, 64, 65, 66, 67, 70, 71, 72, 73, 74, 75, 80, 85, 90, 91, 92, 93 and 99.	IEA Balance builder
Transport Sector	Consumption in the Transport sector covers all transport activity (in mobile engines) regardless of the economic sector to which it is contributing [ISIC Divisions 60, 61 and 62].	IEA Balance builder

CONVERSION FACTORS:						
Bulk Volume:	Loose volume of a material including sp	Unified Bioenergy Terminology - UBET (FAO)				
Dry Matter (d.m.)	Dry matter refers to biomass that has be	IPCC. 2003. Good Practice Guidance for LULUCF – Glossary				
Higher heating value - of dry matter (d.m.) :	Higher heating value (HHV) of dry matte the higher heating value of non-conifero value of bark (coniferous wood, non-con However, in case of a high content of re Source: ÖNORM M 7132. For the conve ==> Further details see <i>klima:aktiv</i> publi	Klima:aktiv Austrian Energy Agency Manual Wood Fuel Parameters Version 1.6. english				
Lower heating value of dry matter:	The lower heating value (LHV) of a fuel conversion from HHV to LHV are explair a lower resin and lignin content, the lowe ÖNORM. For the calculation of the lowe for coniferous wood and non-coniferous MJ/kg higher than that of the wood. Sou ==> Further details see klima:aktiv publ	Klima:aktiv Austrian Energy Agency Manual Wood Fuel Parameters Version 1.6. english				
Mean oven-dry density [kg/m³] (at 0 % H2O)	Mean oven-dry density [kg/m³] (at 0 % H calculation and the respective data sour	Klima:aktiv Austrian Energy Agency Manual Wood Fuel Parameters Version 1.6. english				
Metric Tonne:	1000 Kilograms.					
Moisture Content - wet basis	percentage of the total (wet) weight of th	iomass, defined as the weight of water as a percentage of the weight of biomass. This can be defined on either a wet basis, as a le sample, or a dry basis, as a percentage of the oven dry weight of biomass. Wet basis is usually used for fuel purposes. $Moisture_{wetbasis} = 100x \left(\frac{WetWeight - DryWeight}{WetWeight} \right)$	UK Biomass Energy Centre Klima:aktiv (Austrian Energy Agency) Unified Bioenergy Terminology - UBET (FAO)			
Tonne of oil equivalent	Is the amount of energy released by burning one tonne of crude oil, which is commonly defined as 41.868 GJ. For the conversion from 1000m ³ to ktoe, a factor of 0.208 (=8.72 / 41.868) is used.					
#REF!	Ratio between oven dry mass and fresh NOTE: The Basic Wood Density shown Austrian Energy Agency.	IPCC. 2003. Good Practice Guidance for LULUCF – Glossary				
MISCELLANEOU	S:					
EWC	European Waste Classification		COMMISSION DECISION of 3 May 2000			
FAO	Food and Agriculture Organziation of the	e United Nations	www.fao.org			
IEA	International Energy Agency		www.iea.org			
IPCC	Intergovernmental Panel on Climate Cha	www.ipcc.ch				
IUFRO	International Uniton of Forest Research	www.iufro.org				
LULUCF	Land Use and Land Use Change and Fo	www.unfccc.int				
NAICS	North American Industry Classification S	NAICS 2007				
TBFRA	Temperate and Boreal Forest Resource Assessment					